



www.elektrogas.valve-zone.com

MIXFLOW – ENERGY
80 – 314 Gdańsk,
Al. Grunwaldzka 303
Tel: +48 58 676 55 39
elektrogas@mixflow.com.pl



Autoryzowany Przedstawiciel marki:



VS

**Pressure relief valve
3/4" – 1"**

VS

Pressure relief valve

Contents

Description	2
Features	2
Functioning and application	3
Technical specifications	4
Flow capacity	5
Ordering information	5
Standards and approvals	5

Description

The VS type is a pressure relief valve designed to reduce temporary pressure surge in burning appliances. The shutting-off of automatic valves or non-tightly closing of regulators can cause pressure increase; by releasing that overpressure in a relief line, VS valve enables the system to work properly again.

Features

Valve housing is made of aluminum alloy die-cast.
 Equipped with adjustable spring, so that relief pressure can be precisely set up on site.
 Pipe connections meet group 2.
 Designed for high relief flow.
 Suitable for use with air and non-aggressive gases included in the 1, 2 and 3 families (EN 437). Special versions for aggressive gases (like biogas or COG) are free of non-ferrous metals and provided with rubber part made of FKM (J version).
 Provided with pressure test points on two sides in the inlet chamber to connect manometers, pressure switches or other gas equipments.
 All components are designed to withstand any mechanical, chemical and thermal condition occurring during typical service. Effective impregnation and surface treatments are used to improve mechanical sturdiness, sealing and resistance to corrosion of components.
 Valves are 100% tested and fully warranted.

Functioning and application

In a relief valve inlet pressure acts on one side of a diaphragm, while on the other side there is a spring. Diaphragm is connected to the disc: when force of inlet pressure is higher than spring force, diaphragm moves and disc opens releasing gas in relief line. After discharging pressure surge, inlet pressure gets lower and disc closes again. Relief pressure can be set operating on the spring.




Fig.1

This device is usually installed in gas trains, industrial applications and gas firing systems.

Figure 2 shows an example of installation in combination with other Elektrogas devices.




Fig.2

Technical specifications

Tab. 1

Connections	Threaded F/F	ISO 7-1	Rp3/4 or Rp1
		or ANSI-ASME B1.20 3/4" NPT or 1" NPT	
	Inlet pressure points: G 1/4" (ISO 228) or 1/4" NPT		
Ambient temperature	-15°C ... +60°C	(+5 ... +140°F)	
Inlet pressure - max	3 bar (45 psig)		
Spring colour	Neutral	Orange	Blue
Relief pressure (mbar)	45 – 150	85 – 190	150 – 450
(psig)	0.65 - 2.15	1.25 - 2.75	2.2 - 6.5
Discharge capacity	see charts		
Installation	Horizontal (with settable spring upward) or vertical pipeline.		
Gas type	Air, natural gas, town gas, LPG (gaseous) of families 1,2,3 (EN437). On request special version for biologically produced methane and COG.		
Weight	1.3 Kg		
Materials in contact with gas	Aluminum alloy Stainless steel Plated steel Polyamide Anaerobic adhesive Nitrile rubber (NBR) Polytetrafluoroethylene (PTFE)		
Specifications of J version for Biogas or COG	Max inlet pressure: 1 bar (black spring not available) Seals made of Fluoroelastomer (FPM), instead of NBR <i>It is recommended to check compatibility of gas contents and valve materials before installation.</i>		




Fig.3 (mm)

Flow capacity

With inlet pressure at 115% of set pressure.




Fig. 4

Ordering Information

Tab. 2

VS	3	B	.
Valve type			
VS = relief valve			
Connections			
2 = Rp3/4			
3 = Rp1			
Relief range pressure			
A1 45-150 mbar			
A2 85-190 mbar			
B 150-450 mbar			
C 400-1000 mbar (not for J ver.)			
.			
Special version			
- standard			
N = NPT threads			
.J = version for bio and coke gas			

Standards and approvals

The valves are designed and manufactured according to European Directive on Pressure Equipment 2014/68/EU (cert. PED/0497/3806/20 and PED/0497/2664/13).

Quality Management System is certified according to UNI EN ISO 9001 and the monitoring is carried out by the notified body Kiwa Cermet Italia Spa, Reg.-n° 11989-A



www.elektrogas.valve-zone.com

MIXFLOW – ENERGY

80 – 314 Gdańsk,
Al. Grunwaldzka 303
Tel: +48 58 676 55 39
elektrogas@mixflow.com.pl

